

Supplement to Official Gazette No. 104, Vol. 54, 30th November, 1967—Part B

L.N. 131 of 1967

## MERCHANT SHIPPING ACT 1962

(1962 No. 30)

### The Merchant Shipping (Radio) (Fishing Boat) Rules 1967

*Commencement : 28th February 1966*

In exercise of the powers conferred on me by section 427 of the Merchant Shipping Act 1962, and of all other powers enabling me in that behalf, I hereby make the following rules :—

1.—(1) These Rules may be cited as the Merchant Shipping (Radio) (Fishing Boat) Rules 1967, and shall be deemed to have come into operation on 28th February 1966.

Citation,  
commence-  
ment and  
application.

(2) These Rules shall apply to ships which are sea-going fishing boats of more than 140 feet in length registered in Nigeria.

2.—(1) In these Rules, unless the context otherwise requires, the following expressions have the following meanings respectively—

Interpreta-  
tion, transi-  
tional  
provisions  
and  
savings.

1962 No. 30.

“Act” means the Merchant Shipping Act 1962;

“Connected” means electrically connected;

“Commissioner” means the Commissioner for Transport;

“Existing installation” means

(a) an installation wholly installed before the date on which these rules are deemed to have come into operation; and

(b) an installation part of which was installed before the said date, and the rest of which consists either of parts installed in replacement of identical parts, or parts which comply with the relative requirements of these Rules;

“Fishing boat” means a ship or boat engaged in fishing for profit;

“Interference”, in relation to wireless telegraphy, means the prejudicing by any emission or reflection of electromagnetic energy of the fulfilment of the purposes of the telegraphy (either generally or in part, and, without prejudice to the generality of the preceding words, as respects all, or as respects any, of the recipients or intended recipients of any message, sound or visual image intended to be conveyed by the telegraphy), and the expression “interfer” shall be construed accordingly;

“Length” in relation to a fishing boat means its registered length under the Act;

“Mile” means a nautical mile of 6,080 feet;

“Operating position” in relation to any equipment means the position normally occupied by a person when operating that equipment;

“Radiotelegraph fishing boat” means a fishing boat to which these Rules apply, which is provided with a radiotelegraph installation in compliance with these Rules and which is not a radiotelephone fishing boat;

“Radiotelephone fishing boat” means a fishing boat to which these Rules apply, which is provided with a radiotelephone installation, in compliance with these Rules, and which is not a radiotelegraph fishing boat;

"Radio watch", in the case of radiotelegraph fishing boats, means listening for signalling on the international distress frequency of 500 kc/s, and in the case of radiotelephone fishing boats means listening for signalling on the international distress frequency of 2182 kc/s;

"Silence periods" means the periods of 3 minutes beginning for the purposes of radiotelegraphy at 15 minutes and at 45 minutes after each hour, and for the purposes of radiotelephony at each hour and at 30 minutes after each hour, in every case determined according to Greenwich Mean Time;

In relation to classes of emission :—

"Class A1" means telegraphy by on-off keying without the use of a modulating audio frequency;

"Class A2" means telegraphy by the on-off keying of an amplitude-modulating frequency or audio frequencies, or by the on-off keying of the modulated emission;

"Class A3" means double sideband amplitude modulated telephony; and

"Class B" means damped waves.

(2) The provisions of Schedule 1 of these Rules shall have effect for the purpose of the transition from the law in force before these Rules are deemed to have come into operation to the provisions of these Rules.

(3) Nothing in these Rules shall be construed as enabling any person to be held guilty of an offence thereunder for any act or omission that did not, at the time when it took place, constitute such an offence.

Provision of  
radio  
installation.

3. Every fishing boat to which these Rules apply shall be provided with—

(a) a radiotelegraph installation which shall include the equipment specified in Schedule 2 of these Rules. Provided that the radiotelegraph loudspeaker watchkeeping receiver may be combined with the radiotelegraph auto-alarm equipment specified in Schedule 6 of these Rules in a single instrument, if that instrument is capable of complying with the requirements of Part IV of Schedule 2 and of Schedule 6 of these Rules, or

(b) a radiotelephone installation which shall include the equipment specified in Parts I and II of Schedule 3 of these Rules.

Climatic  
and dura-  
bility test.

4.—(1) All equipment the requirements for which are specified in these Rules, other than test measuring instruments provided in accordance with Rule 12 or paragraph (f) of Rule 21 of these Rules, shall be such that it will be free of mechanical defects and comply with the said requirements—

(a) while undergoing the vibration, dry heat, and low temperature tests required by Schedule 4 of these Rules;

(b) when subjected to the damp heat test required by the said Schedule; and

(c) immediately after undergoing such of the other tests required by the said Schedule as are applicable to the equipment in the circumstances.

(2) Any such equipment which is intended for use in the open or in an open boat shall be such that after undergoing the mould growth test specified in Schedule 4 of these Rules no mould growth will be present on it.

Inter-  
ference  
with  
reception.

5.—(1) At no time while the fishing boat is at sea shall the interference or mechanical noise produced by the radio installation required by these Rules or by other equipment in the fishing boat be sufficient to prevent the effective reception of radio signals by means of such installation.

(2) Any fishing boat to which these Rules apply which is provided with a radiotelegraph installation not being an existing installation shall also be provided with a communal aerial system for all broadcast receivers in respect of which it is impracticable to erect efficient and properly installed aerials which will not interfere with the efficiency of such radiotelegraph installation.

6.—(1) All parts and wiring of the equipment specified in these Rules in which the direct and alternating voltages (other than radio frequency voltages) combine at any time to give an instantaneous voltage greater than 50 volts shall be protected from accidental access.

High  
voltage  
parts.

(2) All parts and wiring of the equipment specified in these Rules (other than the parts and wiring of a rotating machine) in which the direct and alternating voltages (other than radio frequency voltages) combine at any time to give an instantaneous voltage greater than—

(a) 50 volts in the case of equipment specified in Schedule 3 and Schedule 11 of these Rules; or

(b) 250 volts in the case of other equipment,

shall be isolated automatically from all sources of electrical energy when the means of protection are removed.

7. If batteries are provided as a source of electrical energy for any part of the equipment required by these Rules means shall be provided on board every fishing boat to which these Rules apply for the charging of such batteries from the fishing boat's main source of electrical energy.

Charging  
of batteries.

## PART II.—RADIOTELEGRAPHY

8.—(1) Every radiotelegraph installation provided on board a radiotelegraph fishing boat shall be installed in one or more radiotelegraph rooms. The radiotelegraph rooms shall not be used for any purposes other than those associated with the function or duty of the radiotelegraph operator. The radiotelegraph rooms shall be—

Radiotele-  
graph room.

(a) in such a position that there will be no disturbance by extraneous noises or otherwise to the effective reception of radio signals;

(b) as high as practicable in the fishing boat;

(c) of such dimensions as will be sufficient to enable efficient operation at all times of the radiotelegraph equipment installed therein; and

(d) adequately ventilated.

(2) Every radiotelegraph installation provided on board a radiotelegraph fishing boat shall be installed in such a position that it will be protected against disturbance of its effectiveness by water or by extremes of temperature and shall at all times when the fishing boat is at sea be readily accessible both for immediate use and for repair.

(3) Every radiotelegraph room shall be provided with—

(a) an efficient two-way means of calling and voice communication which is independent of the fishing boat's main communication system

and main source of electrical energy and which shall be provided between the place at which the radiotelegraph installation is installed and the place at which the fishing boat is normally navigated ;

(b) a reliable clock, equipped with a dial not less than 5 inches in diameter and a centre seconds hand, the face of which shall be marked to indicate the silence periods. It shall be securely mounted in such a position that the entire dial can be easily and accurately observed from the radiotelegraph operating position and, if the fishing boat is provided with a radiotelegraph auto-alarm equipment, from the position normally occupied by a person testing the radiotelegraph auto-alarm equipment ;

(c) an electric lamp, operated from the source of electrical energy required by Rule 11 (2) of these Rules, or if no reserve source of energy is so required, from the main source of electrical energy for the radiotelegraph installation, and permanently arranged so as to be capable of providing adequate illumination of the operating controls of the radiotelegraph installation and of the clock required by this Rule ;

(d) an additional electric lamp, for use as an inspection lamp, operated from the aforesaid source of electrical energy, and provided with a flexible lead of sufficient length to enable all parts of the radiotelegraph installation to be easily seen ;

(e) a chair capable of being fixed at the radiotelegraph operating position.

(4) A complete list of spare equipment and spare parts carried on board the fishing boat for the maintenance of the radiotelegraph installation shall always be available in every radiotelegraph room and shall indicate where such equipment and parts are kept.

(5) A calibration table or calibration curve for each transmitter and receiver forming part of the radiotelegraph installation shall always be available in a radiotelegraph room, unless the transmitter or receiver, as the case may be, is directly calibrated.

(6) A complete diagram of the wiring of the radiotelegraph installation shall always be available in a radiotelegraph room. Provided that this requirement shall not apply to an existing radiotelegraph installation.

#### Aerials.

9.—(1) Every radiotelegraph fishing boat shall be fitted with a main aerial, and in addition shall carry—

(a) if the main aerial is a supported wire aerial, a spare aerial completely assembled for rapid replacement of the main aerial ;

(b) if the main aerial is not a supported wire aerial, a spare aerial complete with supporting structures and capable of rapid erection while the fishing boat is at-sea.

(2) A rigging plan of the fitted aerial shall be available in the radiotelegraph operating room and shall show the following :—

(a) elevation and plan views of the aerial ;

(b) the measurements of the aerial ; and

(c) the height of the aerial in metres measured in the manner specified in Schedule 10 of these Rules.

#### Range of transmitter.

10.—(1) The normal range of the radiotelegraph transmitter provided in accordance with the foregoing provisions of these Rules shall not be less than 150 miles.



(2) The normal range of a transmitter for the purposes of these Rules shall be determined at the option of the owner of the radiotelegraph fishing boat, either by calculation or by test.

(3) For the purposes of these Rules the normal range of a radiotelegraph transmitter when determined by calculation on a frequency of 500 kc/s, shall be calculated in the manner specified in Schedule 10 of these Rules.

(4) For the purposes of these Rules the normal range of a radiotelegraph transmitter, when determined by test, shall be the distance to which signals can be transmitted by such transmitter over the sea by day under normal conditions on a frequency of 500 kc/s so as to set up at the receiver a total root mean square field strength of at least 50 microvolts per metre.

11.—(1) There shall be available in every radiotelegraph fishing boat while she is at sea and at all reasonable times when she is in port, a supply of electrical energy sufficient for the operation of the radiotelegraph equipment in accordance with these Rules, and for testing purposes and for the charging of any batteries which are a source of electrical energy for the radiotelegraph installation. The rated voltage of the supply of electrical energy shall be maintained within plus or minus 10 per cent. The supply of electrical energy shall, if it is a direct current supply, be of correct polarity. If the aforesaid supply of electrical energy is derived from a battery, a duplicate battery shall be provided.

Supply of  
electrical  
energy.

(2) In the case of a radiotelegraph installation which is not an existing installation, a reserve source of electrical energy derived from a battery, independent of the propelling power of the fishing boat and the fishing boat's electrical installation, shall be provided in the upper part of the fishing boat unless the main source of electrical energy is so situated. The source of electrical energy shall be capable of being brought into immediate operation by means of a switchboard which shall be capable of being illuminated by an electric lamp, and shall be situated in a radiotelegraph room or be readily accessible therefrom. It shall be of such capacity and shall be maintained at all times when at sea in such condition as to be able to supply continuously for a period of 6 hours, whether or not it is in use for any other purpose, a total current equal to the sum of—

(a) the current required to operate the transmitter with the key up ;

(b) three-fifths of the difference between the current required to operate the transmitter with the key down and the current required to operate it with the key up ;

(c) the current required to operate the receiver ; and

(d) the current consumed by the lamps required by this paragraph and by paragraph (c) of Rule 8 (3) of these Rules.

(3) Any reserve source of electrical energy provided under paragraph (2) of this Rule shall not be used at any time except for the operation of—

(a) the radiotelegraph installation ;

(b) the lamps required by paragraph (2) of this Rule and by paragraphs (c) and (d) of Rule 8 (3) of these Rules ;

(c) the automatic keying device ;

(d) a radiotelegraph auto-alarm equipment ;

(e) a direction-finder, if fitted.

(4) Notwithstanding the provisions of paragraph (3) of this Rule, in any fishing boat the reserve source of electrical energy required by paragraph (2) of this Rule may if the Commissioner so permits be used to supply any low-power emergency circuits which are wholly confined to the upper part of the fishing boat. Provided that such circuits shall be capable of being readily disconnected and that the said source shall be capable of supplying the additional load or loads without falling below the capacity required by paragraph (2) of this Rule.

Tools,  
measuring  
instru-  
ments, spare  
parts, etc.

12. Every radiotelegraph fishing boat shall be provided with the tools, measuring instruments, spare parts and other material specified in Part I of Schedule 5 of these Rules.

Provision  
of radio-  
telegraph  
operators.

13.—(1) Every radiotelegraph fishing boat which upon proceeding to sea is not provided with a radiotelegraph auto-alarm equipment complying with the requirements specified in Schedule 6 of these Rules shall be provided with radiotelegraph operators as follows:—

(a) one radiotelegraph operator if such fishing boat is to be at sea for not more than 8 hours after leaving port;

(b) two radiotelegraph operators if such fishing boat is to be at sea for more than 8 hours but not more than 48 hours after leaving port; or

(c) three radiotelegraph operators if such fishing boat is to be at sea for more than 48 hours after leaving port.

(2) Every radiotelegraph fishing boat which upon proceeding to sea is provided with a radiotelegraph auto-alarm equipment complying with the requirements specified in Schedule 6 of these Rules shall be provided with at least one radiotelegraph operator.

Qualifica-  
tions of  
radio-  
telegraph  
operators.

14.—(1) For the purposes of these Rules no person shall be qualified to be a radiotelegraph operator on board a fishing boat to which these Rules apply unless he holds a valid certificate of proficiency or competence in radiotelegraph of the first, second or special class granted by or on behalf of the Commissioner for Communications as issuing authority for the purposes hereof or an equivalent certificate granted by the Postmaster-General of the United Kingdom or by a competent authority empowered to do so in any part of the Commonwealth or the Irish Republic.

(2) For the purposes of paragraph (1) of this Rule no certificate of proficiency or competence shall be deemed to be valid at any date if granted more than 2 years before that date and either—

(a) the holder's periods of experience do not total three months, or

(b) the holder's last experience was more than 2 years before that date, unless the holder satisfies the issuing authority by re-examination or otherwise that he still possesses all the qualifications described in his certificate.

(3) For the purposes of paragraph (2) above the expression "experience" means experience as the operator of radiotelegraph apparatus—

(a) at sea, as a radio officer or a radiotelegraph operator, or

(b) on land, as an operator at a radiotelegraph station maintained on land for communication with ships.

Radio  
watch.

15.—(1) Subject to paragraphs (1) and (2) of Rule 16 of these Rules radio watch shall be maintained at sea on board every radiotelegraph fishing boat by a radiotelegraph operator as follows :—

(a) if such fishing boat upon proceeding to sea is not provided with a radiotelegraph auto-alarm equipment complying with the requirements specified in Schedule 6 of these Rules, a continuous watch ;

(b) if such fishing boat upon proceeding to sea is provided with a radiotelegraph auto-alarm equipment as aforesaid, a watch of at least eight hours a day at the times specified in Column 5 of Schedule 7 of these Rules in relation to the zone in which the fishing boat then is.

(2) Any radiotelegraph auto-alarm equipment provided on board a radiotelegraph fishing boat shall be in operation at all times at which a radio watch is not maintained.

16.—(1) Every radiotelegraph operator on board a radiotelegraph fishing boat shall keep watch by means of headphone reception throughout his period of duty except when another radiotelegraph operator keeps radio watch by headphone reception. Provided that—

Watch-  
keeping  
and other  
radio duties  
of radio-  
telegraph  
operators.

(a) radio watch may be maintained by means of loud-speaker reception,  
or

(b) if loud-speaker reception is impracticable radio watch may be dispensed with except during a silence period,  
for such periods as may be necessary to enable the radiotelegraph operator to perform other duties in compliance with these Rules or to handle traffic on another frequency.

(2) Notwithstanding the provisions of paragraph (1) of this Rule, radio watch may be dispensed with when the radiotelegraph fishing boat is actually engaged in fishing, if it is provided with a radiotelegraph auto-alarm equipment complying with the requirements specified in Schedule 6 of these Rules, and that equipment is put into operation in accordance with paragraph (3) of this Rule.

(3) Every radiotelegraph operator on board a radiotelegraph fishing boat provided with a radiotelegraph auto-alarm equipment complying with the requirements specified in Schedule 6 of these Rules shall, whenever radio watch ceases to be maintained during or at the end of his period of duty, connect the radiotelegraph auto-alarm equipment with the fishing boat's main aerial or with any other efficient aerial and shall put the radiotelegraph auto-alarm equipment into operation. Every radiotelegraph operator who leaves a radiotelegraph auto-alarm equipment in operation when he goes off duty shall before going off duty—

(a) test the efficiency of the radiotelegraph auto-alarm equipment ;

(b) immediately inform the master or the officer in charge of the navigation of the fishing boat if the radiotelegraph auto-alarm equipment is found not to be operating effectively.

(4) Every such radiotelegraph operator who finds a radiotelegraph auto-alarm equipment connected to an aerial when he goes on duty shall immediately test the efficiency of the radiotelegraph auto-alarm equipment before making any adjustment thereto.

(5) While a radiotelegraph fishing boat is at sea, the radiotelegraph operator, or if there is more than one, the first radiotelegraph operator, shall cause the following tests to be made :—

(a) a test once a day by voltmeter and once a month by hydrometer of any batteries which are a source of electrical energy for the radio-telegraph installation ;

(b) a test once a day of any other source of electrical energy ;

(c) a test once a day of the audible alarm circuits and of the bells forming part of the radiotelegraph auto-alarm equipment ; and

(d) a test once a day to check the proper functioning of the radiotelegraph auto-alarm receiver connected to its normal aerial, by listening to signals received by means of that receiver, and by comparing them with similar signals received on a frequency of 500 kc/s by means of the main receiver.

(6) While a radiotelegraph fishing boat is at sea, the radiotelegraph operator or, if there is more than one, the first radiotelegraph operator, shall take all steps within his power to cause the equipment referred to in these Rules to be properly maintained and when necessary to be repaired and adjusted. Such operator shall arrange for all batteries, being a source of electrical energy for any part of the radiotelegraph installation, which are found not to be fully charged to be brought up to that condition as soon as possible.

Radiotele-  
graph log.

17.—(1) A radiotelegraph log-book in the form specified in Schedule 8 to these Rules shall be kept in a radiotelegraph room on board every radiotelegraph fishing boat and shall be available for inspection by any person authorised in that behalf by the Commissioner.

(2) Every radiotelegraph operator on board such a fishing boat shall, when on duty, enter in such log-book :—

(a) his name ;

(b) the times at which he goes on duty and off duty ;

(c) the identifying number of each message transmitted by him, or received by him, together with the time and date of such transmission or reception, the station to which each message is transmitted by him and the station from which each message is received by him ; and

(d) a record of all incidents occurring during his period of duty which relate to the radiotelegraph installation and the operation thereof and which would appear to him to be of importance to the safety of life at sea ; in particular he shall make the following entries :—

(i) the full text of all messages transmitted by him or received by him which relate to immediate assistance required by persons in distress at or above the sea ;

(ii) the full text of all messages transmitted by him or received by him which are preceded by a signal in general international use as an urgency signal or a safety signal ;

(iii) a record of the radio watch maintained by him during each of the silence periods ;

(iv) a record of any incident occurring during his period of duty which affects the efficiency of the radiotelegraph installation ; and

(v) a record of tests conducted by him in accordance with paragraphs (3) and (4) of Rule 16 of these Rules, and of the result of such tests.



(3) The radiotelegraph operator, or, if there is more than one, the first radiotelegraph operator shall cause the following entries to be made in such log-book :—

(a) a record of the tests conducted in accordance with Rule 16 (5) and Rule 27 (1) of these Rules ;

(b) a record of the charging of any batteries used as a source of electrical energy for the radiotelegraph installation ; and

(c) if the radiotelegraph fishing boat is provided with a radiotelegraph auto-alarm equipment details of any failure or repair thereof.

(4) The radiotelegraph operator, or, if there is more than one, the first radiotelegraph operator shall cause an entry to be made in such log-book recording the time shown by the clock in each radiotelegraph room in comparison with Greenwich Mean Time and any correction made in respect of that clock at least once a day when the station is open.

(5) The radiotelegraph operator, or, if there is more than one, the first radiotelegraph operator shall, if the radiotelegraph fishing boat's rules permit, cause any entry to be made in such log-book recording in latitude and longitude, or by reference to a place, the approximate position of such fishing boat at least once per day when the station is open.

(6) If there is more than one radiotelegraph operator, the first radiotelegraph operator shall inspect and sign each day the entries for that day in such log-book.

(7) The master of every radiotelegraph fishing boat shall inspect and sign each day's entries in such log-book.

(8) Section 134 of the Act (which provides for the delivery of the official log-book to the Superintendent) and section 135 thereof (which provides among other things for the custody of the official log-book) shall apply to the radiotelegraph log-book as they apply to the official log-book.

### PART III.—RADIOTELEPHONY

18.—(1) Every radiotelephone fishing boat shall be fitted with an aerial, and in addition shall carry—

Aerial.

(a) if the main aerial is a supported wire aerial, a spare aerial completely assembled for rapid replacement of the main aerial ;

(b) if the main aerial is not a supported wire aerial, a spare aerial complete with supporting structures and capable of rapid erection while the fishing boat is at sea.

(2) A rigging plan of the fitted aerial shall be available on board and shall show the following :—

(a) elevation and plan views of the aerial ;

(b) the measurements of the aerial ;

(c) the height of the aerial in metres measured in the manner specified in Rule 19 (3) of these Rules.

19.—(1) The normal range of a radiotelephone transmitter provided in accordance with the foregoing provisions of these Rules shall not be less than 150 miles.

Range of  
trans-  
mitter.

(2) The normal range of a radiotelephone transmitter for the purpose of these Rules shall be determined at the option of the owner of the radiotelephone fishing boat either by calculation or by test.

(3) For the purposes of these Rules the normal range of a radiotelephone transmitter, when determined by calculation on a frequency of 2182 kc/s, shall be calculated by ascertaining the product of the root mean square current in amperes at the base of the aerial and the maximum height of the aerial measured from the lead-out insulator. The transmitter shall be deemed to comply with the requirements of this Rule if the product so ascertained is not less than—

(a) 7.5 metre-amperes if the aerial has a horizontal top-length of not less than one-half of its maximum height measured from the lead-out insulator ;

(b) 12.8 metre-amperes in the case of any other aerial.

(4) For the purposes of these Rules the normal range of a radiotelephone transmitter, when determined by test, shall be the distance to which signals can be transmitted by such transmitter over the sea by day under normal conditions on a frequency of 2182 kc/s so as to set up at the receiver by the unmodulated carrier a total root mean square field strength of at least 25 microvolts per metre.

Supply of  
electrical  
energy.

20.—(1) There shall be available in every radiotelephone fishing boat while she is at sea and at all reasonable times when she is in port, a supply of electrical energy sufficient to operate the radiotelephone installation in accordance with these Rules, and for testing purposes and for the charging of any batteries which are a source of electrical energy for the radiotelephone installation. The supply of electrical energy shall if it is a direct current supply be of correct polarity. In the case of a radiotelephone installation which is not an existing installation a reserve source of electrical energy derived from a battery shall be provided in the upper part of the radio telephone fishing boat unless the main source of electrical energy is so situated. Each source of electrical energy provided in compliance with this Rule shall be of such capacity as to be able to supply continuously for a period of six hours a total current equal to the sum of—

(a) one-half of the current required to operate the radiotelephone transmitter for the transmission of speech ;

(b) the current required to operate the radio-telephone receiver ; and

(c) the current consumed by the electric lamp required by paragraph (d) of Rule 21 of these Rules.

(2) If a single battery is provided for the foregoing purpose means shall also be provided for either—

(a) operating the radiotelephone installation from the radiotelephone fishing boat's main source of electrical energy, or

(b) float-charging the battery while it is in use, in which case there shall be adequate protection against voltage rise.

Such means shall be so designed as not to require the earthing of the radiotelephone fishing boat's main source of electrical energy, and adequate filtering shall where necessary be provided to prevent mainsborne interference from entering the radio equipment.

(3) A reserve source of electrical energy provided in compliance with paragraph (1) of this Rule shall not be used at any time except for the operation of—

(a) the radiotelephone installation ;

(b) the electric lamp required by paragraph (d) of Rule 21 of these Rules.

(4) Notwithstanding the provisions of paragraph (3) of this Rule, in every radiotelephone fishing boat a reserve source of electrical energy provided in compliance with paragraph (1) of this Rule may if the Commissioner so permits be used to supply—

(a) a direction-finder, if fitted ; and

(b) low-power emergency circuits which are wholly confined to the upper part of the fishing boat ;

on condition that the said source is capable of supplying the additional load or loads without falling below the capacity required by paragraph (1) of this Rule.

(5) When any battery provided for the radiotelephone installation is not in use, it shall be capable of being fully charged within a period of not more than 16 hours by the means for charging required by Rule 7 of these Rules.

21. The following provisions shall apply to every radiotelephone fishing boat :—

**Miscellaneous  
requirements.**

(a) The radiotelephone installation required by these Rules shall be installed—

(i) as high as practicable in the radiotelephone fishing boat ; and

(ii) in a position where there is least disturbance by extraneous noise or otherwise to the effective reception of radio signals.

(b) An efficient two-way means of communication, independent of the radiotelephone fishing boat's main communication system and main source of electrical energy, shall be provided between the place at which the aforesaid radiotelephone installation is installed and any other place from which the fishing boat is normally navigated.

(c) A reliable clock shall be securely mounted in such a position that the entire dial can be easily and accurately observed from the operating position of the aforesaid radiotelephone installation.

(d) A reliable emergency lamp shall be provided which shall be independent of the main lighting system of radiotelephone fishing boat, and shall be arranged so as to be capable of providing adequate illumination of the aforesaid radiotelephone installation, the clock required by paragraph (c) of this Rule and the card of instructions required by paragraph (e) of this Rule. If a reserve source of electrical energy is provided in compliance with Rule 20 of these Rules the emergency lamp shall be an electric lamp operated from the aforesaid source.

(e) A card of instructions giving a clear summary of the radiotelephone distress, urgency and safety procedures shall be displayed in full view of the radiotelephone operating position.

(f) The tools, measuring instrument, spare parts and other material specified in Part II of Schedule 5 of these Rules shall be provided and shall be kept readily available.

Provision  
and  
qualifica-  
tions of  
radiotele-  
phone  
operator.

22.—(1) Every radiotelephone fishing boat to which these Rules apply shall be provided with at least one radiotelephone operator.

(2) For the purposes of these Rules no person shall be qualified to be a radiotelephone operator on board a radiotelephone fishing boat registered in Nigeria unless he holds a valid certificate of proficiency or competence in radiotelephony or radiotelegraphy granted by or on behalf of the Commissioner for Communications or an equivalent certificate granted by the Postmaster General of the United Kingdom or by a competent authority empowered to do so in any part of the Commonwealth or the Irish Republic.

Radio  
watch.

23.—(1) Subject to the provisions of paragraph (2) of this Rule, while a radiotelephone fishing boat is at sea continuous radio watch shall be maintained at the operating position or at the place on board from which the fishing boat is normally navigated. Such watch shall be kept by a radiotelephone operator, or by means of loudspeaker reception by the master or by an officer or member of the crew appointed to that duty by the master.

(2) Radio watch may be discontinued—

(a) when the receiver forming part of the radiotelephone installation required by Rule 3 of these Rules is being used for traffic on a frequency other than 2182 kc/s and a second receiver complying with the requirements specified in Part III of Schedule 3 of these Rules is not available ; or

(b) when, in the opinion of the master of the radiotelephone fishing boat, conditions are such that maintenance of radio watch would interfere with the safe navigation of such fishing boat.

(3) Notwithstanding the provisions of sub-paragraph (b) of the preceding paragraph radio watch shall, as far as practicable, be maintained during the silence periods.

Duties of  
radio-  
telephone  
operator.

24.—(1) Every radiotelephone operator shall be familiar with the radiotelephone distress, urgency and safety procedures as given in the card of instructions required by paragraph (e) of Rule 21 of these Rules.

(2) While a radiotelephone fishing boat is at sea, the radiotelephone operator, or if there is more than one, one designated by the master, shall arrange for any batteries which are a source of electrical energy for the radiotelephone installation to be tested once a day and brought up to fully-charged condition as soon as possible.

Radio-  
telephone  
log.

25.—(1) A radiotelephone log-book in the form specified in Schedule 9 of these Rules shall be kept at the place where radio watch is maintained in every radiotelephone fishing boat, and shall be available for inspection by any person authorised in that behalf by the Commissioner.

(2) Every radiotelephone operator shall, when keeping radio watch in compliance with Rule 23 (1) of these Rules, enter in such log-book :—

(a) his name ;

(b) the times at which he begins and ends his periods of radio watch ;

(c) the time at which radio watch is for any reason discontinued, together with the reason, and the time at which radio watch is resumed ;

(d) a summary of communications exchanged between the fishing boat and coast stations or other ship stations ;



(e) a record of all incidents occurring during his period of radio watch which relate to the radiotelephone installation and the operation thereof and which appear to him to be of importance to the safety of life at sea ; in particular, he shall make the following entries :—

(i) the general sense of all messages transmitted by him and received by him which relate to immediate assistance required by persons in distress at or above the sea ;

(ii) the general sense of all messages transmitted by him and received by him which are preceded by a signal in general international use as an urgency signal or a safety signal ;

(iii) a record of the radio watch maintained by him during each of the silence periods ;

(iv) a record of any incident occurring during his period of radio watch which affects the efficiency of the radiotelephone installation ; and

(v) if the fishing boat's rules permit a record in latitude and longitude, or by reference to a place, of the approximate position of the fishing boat at least once per day when the station is open.

(3) Every radiotelephone operator shall enter in such log-book a record of the tests conducted in accordance with Rule 24 (2) and Rule 27 (3) of these Rules.

(4) The master and every officer or member of the crew shall, when keeping radio watch in compliance with Rule 23 (1) of these Rules, enter in such log-book :—

(a) his name ;

(b) the times at which he begins and ends his periods of radio watch ;

(c) the time at which radio watch is for any reason discontinued, together with the reason, and the time radio watch is resumed ;

(d) a record of all incidents occurring during his period of watch which relate to the radiotelephone installation and the operation thereof and which appear to him to be of importance to the safety of life at sea ; in particular, he shall make the following entries :—

(i) the general sense of all messages received by him which relate to immediate assistance required by persons in distress at or above the sea ;

(ii) the general sense of all messages received by him which are preceded by a signal in general international use as an urgency signal or a safety signal ;

(iii) a record of any incident occurring during his period of radio watch which affects the efficiency of the radiotelephone installation ; and

(iv) if the fishing boat's rules permit a record in latitude and longitude, or by reference to a place, of the approximate position of the fishing boat at least once per day when the station is open.

(5) The radiotelephone operator, or, if there is more than one, one designated by the master, shall inspect and sign each day the entries for that day in such log-book.

(6) The master of every radiotelephone fishing boat shall inspect and sign each day's entries in such log-book.

(7) Section 134 of the Act (which provides for the delivery of the official log-book to the Superintendent) and section 135 thereof (which provides among other things for the custody of the official log-book) shall apply to the radiotelephone log-book as they apply to the official log-book.

#### PART IV. — RADIO EQUIPMENT FOR SURVIVAL CRAFT

26. Notwithstanding the provisions of Rule 1 (2) of these Rules the equipment required by Rule 16 (8) of the Merchant Shipping (Life-Saving Appliances) Rules 1967 to comply with the requirements of these Rules shall comply with the specification set forth in Schedule II of these Rules.

27.—(1) When a radiotelegraph fishing boat, provided with the equipment referred to in Rule 26 of these Rules is at sea the radiotelegraph operator, or if there is more than one, the first radiotelegraph operator shall, at least once every 7 days, test the transmitter forming part of such equipment with its artificial aerial.

(2) The radiotelegraph operator making the test referred to in paragraph (1) of this Rule shall enter the results in the radiotelegraph log-book.

(3) When a radiotelephone fishing boat, provided with the equipment referred to in Rule 26 of these Rules, is at sea the radiotelephone operator, or if there is more than one, one designated by the master shall, at least once every 7 days, test the transmitter forming part of such equipment with its artificial aerial.

(4) The radiotelephone operator making the test referred to in paragraph (3) of this Rule shall enter the results in the radiotelephone log-book.

### SCHEDULES

#### Rule 2 (2)

#### SCHEDULE I

##### TRANSITIONAL PROVISIONS

1. As to Rule 3.—Subject to the provisions of paragraph 2 of this Schedule any fishing boat which is provided with radiotelegraph equipment forming part of an existing installation or which is installed before 28th February 1968 shall not be required to be provided with the equipment specified in Schedule 2 of these Rules.

2. As to Rule 3.—Nothing in Rule 3 of these Rules shall require the automatic keying device of a radiotelegraph installation to comply with the requirements of Part III of Schedule 2 of these Rules before 28th February 1968.

3. As to Rule 3.—Any fishing boat which is provided with radiotelephone equipment forming part of an existing installation or which is installed before 28th February 1968 shall not be required to be provided with the equipment specified in Part I of Schedule 3 of these Rules.

4. As to Rule 3.—Nothing in Rule 3 of these Rules shall require the device for generating the radiotelephone alarm signal specified in Part II of Schedule 3 of these Rules to be provided before 28th February 1967.

Portable  
radio  
equipment  
for survival  
craft.  
L.N. 72 of  
1967.

Test of  
portable  
radio  
equipment.

5. As to Rule 4.—Nothing in Rule 4 of these Rules shall apply to any equipment forming part of an existing installation or which is installed before 28th February 1968.

6. As to Rule 6.—Nothing in Rule 6 of these Rules shall require any parts or wiring in an existing installation to be isolated automatically from all sources of electrical energy when the means of protection referred to therein are removed.

7. As to Rule 10.—Any transmitter forming part of an existing installation or which is installed before 28th February 1968 shall be deemed to comply with this Rule if its normal range is not less than 75 miles.

8. As to Rule 19.—Nothing in Rule 19 of these Rules shall require the transmitter forming part of an existing installation to exceed a normal range of 75 miles. The transmitter shall be deemed to comply with this provision if the product ascertained in the manner specified in paragraph (3) of the aforesaid Rule is not less than—

(a) 3.25 metre-amperes if the aerial has a horizontal top-length of not less than one-half of its maximum height measured from the lead-out insulator ;

(b) 5.5 metre-amperes in the case of any other aerial.

## SCHEDULE 2

Rule. 3.

### RADIOTELEGRAPH INSTALLATION

#### Part I.—Radiotelegraph Transmitter

1. The radiotelegraph transmitter (in this Part of the Schedule referred to as "the transmitter") shall be provided with any equipment which may be necessary to enable it to be operated from the source of electrical energy referred to in Rule II (1) of these Rules, and shall be capable of being tuned to the main aerial referred to in Rule 9 of these Rules.

General.

2. The transmitter shall be capable of transmitting Class A 1 and Class A 2 emissions on 500 kc/s and at least four other spot frequencies in the range 405 to 525 kc/s.

Frequency ranges and classes of emission.

3. When Class A 2 emissions are being transmitted, the transmitter shall have a depth of modulation of not less than 70 per cent and a note frequency between 450 and 1350 c/s.

Modulation.

4.—(1) It shall be possible for an operator to change the transmitter from operation on any frequency to operation on any other frequency in a period not exceeding 10 seconds.

Operating facilities.

(2) The transmitter shall be ready for fullpower operation within 60 seconds of switching on.

(3) The transmitter shall be capable of being used in conjunction with the automatic keying device specified in Part III of this Schedule.

(4) Means shall be incorporated to provide, in conjunction with an associated receiver, listening—through facilities at normal signalling speeds.

*Part II.—Radiotelegraph Receiver*

## General.

1.—(1) The radiotelegraph receiver (in this Part of this Schedule referred to as "the receiver") shall be capable of being operated from the source of electrical energy referred to in Rule II (1) of these Rules.

(2) The receiver shall consist of a single unit or of separate units each of which is capable of reception on one or more sections of the frequency range specified in paragraph 3 of this Part of this Schedule. Each unit of the receiver shall bear a plate stating the frequency range it is intended to cover.

(3) The receiver shall not employ any vibrators or primary batteries.

## Frequency ranges and classes of emission.

2. The receiver shall be capable of receiving signals within the frequency ranges and of the classes of emission specified in the following table.

<i>Frequency Range (inclusive)</i>	<i>Class of Emission</i>
15 kc/s-160 kc/s	A 1
160 kc/s-1500 kc/s	A 1, A 2
1500 kc/s-4 Mc/s	A 1, A 2, A 3
4 Mc/s-28 Mc/s	A 1, A 2, A 3

## Reception facilities.

3. The receiver shall be capable of headphone and loudspeaker reception throughout the frequency range specified in paragraph 3 of this Part of this Schedule. The loudspeaker shall be rendered inoperative when reception is by headphones.

## Sensitivity.

4. The receiver shall have sufficient sensitivity to produce signals in headphones or by means of a loudspeaker when the receiver input is as low as 50 microvolts.

5. The receiver shall be provided with—

## Controls.

(1) means for reducing the receiver sensitivity when the telegraph key is depressed so as to permit listening-through at normal signalling speeds when an associated transmitter is operating in the same frequency band ;

(2) manual controls, as necessary, for the adjustment of radio and/or intermediate frequency gain and of audio frequency gain ;

(3) means for enabling the operator to tune to any frequency in the same maritime mobile band within five seconds and within 15 seconds if the frequencies are in different bands ;

(4) a tuning scale calibrated directly in frequency ;

(5) a logging scale or other approved means for accurate resetting of tune ; and

(6) a fine control, the knob of which shall be at least two inches in diameter, unless the frequency is adjustable in steps of 100 c/s or less.

## Radiation.

6. The receiver when in use shall not produce a field exceeding 0.1 microvolt per metre at a distance of one mile from the receiver.



*Part III.—Radiotelegraph Automatic Keying Device*

SCH. 2.

1.—(1) The radiotelegraph automatic keying device (in this Part of this Schedule referred to as "the device") shall be capable of sending automatically the signals specified in paragraph 3 of this Part of this Schedule when switched into circuit in place of the manual key.

General.

(2) Means shall be provided for quickly connecting and disconnecting the device, as required, to and from the radiotelegraph transmitter and the radiotelegraph auto-alarm test signal generator referred to in paragraph 5 of Schedule 6 of these Rules.

(3) If the device is electrically operated it shall be suitable for operation from the reserve source of electrical energy required by Rule 11 (2) of these Rules.

2. The device shall be capable of keying only the following signals when switched into circuit :—

Signals.

(1) the radiotelegraph alarm signal consisting of twelve four second dashes separated by one second spaces, the length of the dashes and spaces being maintained within a tolerance of plus or minus 0.2 second ;

(2) the radiotelegraph distress call consisting of the following signals in the following order :—

(a) the radiotelegraphy distress signal SOS, sent three times,

(b) the word DE,

(c) the fishing boat's call sign, sent three times, and

(d) two dashes, each of 10 to 15 seconds duration.

3. The device shall be suitable for operation by an unskilled person.

Operating facilities.

*Part IV.—Radiotelegraph Loudspeaker Watchkeeping Receiver*

1.—(1) The radiotelegraph loudspeaker watchkeeping receiver (in this Part of this Schedule referred to as "the receiver") shall be fixed in tune on a frequency of 500 kc/s and shall be suitable for the reception of Class A2 emissions in the range 496 to 504 kc/s.

General.

(2) The receiver shall include a loudspeaker.

(3) Provision shall be made for protecting the receiver when the fishing boat's transmitter is radiating on 500 kc/s.

2. The selectivity preceding the final detector shall satisfy the following requirements with the automatic gain control inoperative :—

Selectivity.

<i>Frequency (kc/s)</i>	<i>Discrimination (db relative to Maximum Response)</i>
496 to 504	Not more than 3
Below 487 and above 513	At least 40
Below 475 and above 525	At least 80

SCH. 2.  
Standard  
output  
level.

3. The standard audio frequency output level shall be 50 milliwatts into a resistance substantially equal to the modulus of the impedance of the loudspeaker at 1000 c/s.

Controls.

4. —(1) The receiver shall be provided with a manual gain control and an automatic gain control. Subject to the provisions of sub-paragraph 2 of this paragraph no controls other than a manual gain control and an on-off switch shall be available at the exterior of the receiver.

(2) If the receiver facilities are incorporated in a combined receiver that is to say in a radiotelegraph auto-alarm equipment complying with the requirements of Schedule 6 of these Rules—

(a) it shall be possible readily to set the combined receiver to the loudspeaker watchkeeping condition. If this setting is not by means of a single control, a positive indication shall be given by means of a lamp or lamps when the receiver is in the 500 kc/s loudspeaker watchkeeping condition;

(b) when the combined receiver is in the loudspeaker watchkeeping condition, controls of the said radiotelegraph auto-alarm equipment, other than those referred to in sub-paragraph (1) of this paragraph, shall not affect its operation; and

(c) controls of the combined receiver which affect the operation when in a loudspeaker watchkeeping condition shall be clearly labelled.

Radiation.

5. The receiver when in use shall not produce a field exceeding 0.1 micro-volt per metre at a distance of one mile from the receiver.

## SCHEDULE 3

Rule 3

### RADIOTELEPHONE INSTALLATION

#### *Part I.—Main Radiotelephone Installation*

General.

1. In this Part of this Schedule the expression "the equipment" includes a radiotelephone transmitter and receiver and all other equipment necessary for the operation of the installation but does not include an aerial or a source of electrical energy.

Frequency  
ranges and  
classes of  
emission.

2.—(1) The equipment shall be capable of transmitting Class A3 emissions on a frequency of 2182 kc/s and of transmitting telephony on at least eight other spot frequencies.

(2) The equipment shall be capable of receiving Class A2 and A3 emissions on a frequency of 2182 kc/s and at least 20 other spot frequencies in the range 1605 to 3800 kc/s.

(3) Independent selection of transmit and receive frequencies shall be provided.

Transmitter.

3.—(1) The transmitter shall be provided with a device for generating the radiotelephone alarm signal specified in Part II of this Schedule.

(2) In normal operation the transmitter shall have a depth of modulation on 2182 kc/s of not less than 70 per cent at peak intensity.

Receiver.

4.—(1) The receiver shall have sufficient sensitivity to produce signals by means of a loudspeaker when the receiver input is as low as 50 microvolts.

(2) The receiver when in use shall not produce a field exceeding 0.1 microvolt per metre at a distance of one mile from the receiver.

Sch. 3.

5. The equipment shall be capable of operation from the source of electrical energy required by Rule 20 of these Rules.

Source of electrical energy.

6.—(1) The equipment shall be capable of being changed rapidly from "transmit" to "receive" and vice versa and means shall be provided for protecting the receiver from damage when the equipment is transmitting.

Operating facilities.

(2) It shall be possible for an operator to change the transmitter from operation on any frequency to operation on any other frequency in a period not exceeding 10 seconds.

(3) The transmitter shall be ready for full-power operation within 60 seconds of switching on.

(4) The receiver shall have provision for both telephone receiver and loudspeaker reception.

7. All controls shall be of such size as to permit normal adjustments to be performed by a person wearing thick gloves.

Controls.

## *Part II.—Radiotelephone Alarm Signal Generating Device*

1.—(1) The radiotelephone alarm signal generating device (in this Part of this Schedule referred to as "the device") shall be capable of generating the radiotelephone alarm signal specified in paragraph 3 of this Part of this Schedule.

General.

(2) The device shall be ready to generate the radiotelephone alarm signal within a period of 30 seconds from the time the device is energised and shall be capable of generating for a period of not less than 30 and not more than 60 seconds.

(3) After generating the radiotelephone alarm signal the device shall be ready to repeat the signal after an interval of not more than two minutes.

(4) Means shall be provided so that the device can be taken out of service at any time.

2. The radiotelephone alarm signal referred to in sub-paragraph (1) of paragraph 2 of this Part of this Schedule shall consist of two substantially sinusoidal tones, one having a frequency of 2200 c/s plus or minus 1.5 per cent and the other 1300 c/s plus or minus 1.5 per cent, produced alternately; the duration of each tone shall be 250 milliseconds plus or minus 50 milliseconds the interval between successive tones shall not exceed 50 milliseconds. The ratio of the amplitude of the stronger tone to that of the weaker shall be within the range 1 to 1.2.

Alarm signal.

3.—(1) Not more than two operating controls shall be available at the exterior of the device. Each control shall be clearly labelled to show its purpose and shall be such as to permit normal operation to be carried out by a person wearing thick gloves.

Controls.

(2) Controls, where provided, for the adjustment of frequency, duration or level of the signal elements shall be preset controls not available at the exterior of the device.

*Part III.—Radiotelephone Loudspeaker Watchkeeping Receiver*

## General.

1.—(1) The radiotelephone loudspeaker watchkeeping receiver (in this Part of this Schedule referred to as "the receiver") shall be fixed in tune on a frequency of 2182 kc/s and shall be suitable for the reception of Class A2 and A3 emissions except when the fishing boat's own radiotelephone transmitter is radiating on 2182 kc/s.

(2) The receiver shall include a loudspeaker.

(3) Provision shall be made for protecting the receiver and muting its output when the fishing boat's transmitter is radiating on 2182 kc/s.

## Selectivity.

2. The selectivity preceding the detector shall satisfy the following requirements :—

<i>Frequency (kc/s)</i>	<i>Discrimination (db relative to Maximum Response)</i>
2178.5 to 2185.5 inclusive	Not more than 6
Below 2172 and above 2192	At least 30
Below 2162 and above 2202	At least 60
Below 2142 and above 2222	At least 80

## Sensitivity

3. The receiver shall have sufficient sensitivity to produce signals by means of a loudspeaker when the receiver input is as low as 50 microvolts.

## Controls.

4.—(1) The receiver shall be provided with—

(a) a manual control labelled "RANGE" for the adjustment of radio frequency or intermediate frequency gain, or both ;

(b) a preset control not available at the exterior of the receiver, for the adjustment of radio frequency or intermediate frequency gain, or both ;

(c) a manual control labelled "VOLUME" for the adjustment of audio frequency gain ; and

(d) a preset control not available at the exterior of the receiver, for the adjustment of audio frequency gain.

(2) With the exception of the controls specified in sub-paragraphs (a) and (c) of the preceding paragraph and a receiver on-off switch, no other control shall be available at the exterior of the receiver.

## Radiation.

5. The receiver when in use shall not produce a field exceeding 0.1 micro-volt per metre at a distance of one mile from the receiver.

## SCHEDULE 4

Rule 4

## CLIMATIC AND DURABILITY TESTS

1. In this Schedule—

(1) references to Class B equipment shall be construed as references to equipment appropriated for use only below deck or in a deckhouse or other similar compartment ;

## Interpretation.



(2) references to Class X equipment shall be construed as references to equipment appropriated for use or storage in the open or in an open boat.

Sch. 4.

2. Class B and Class X equipment shall be subjected to tests conducted in the order in which they appear in the following Table :—

Tests to be conducted.

TABLE

<i>Nature of Test</i>	<i>Classes of Equipment to which the test shall be applied</i>
Visual Inspection and Performance Test	B and X
Inspection under Vibration	B and X
Bump Test	B and X
Dry Heat Cycle	B and X
Damp Heat Cycle	B and X
Low Temperature Cycle	B and X
Rain Test	X
Immersion Test	X
Corrosion Test	B and X
Mould Growth Test	X
Visual Inspection and Performance Test	B and X

3. The tests referred to in paragraph 2 of this Schedule shall be conducted respectively in the manner described in the Performance Specification for the Climatic and Durability Testing of Marine Radio Equipment 1965 issued by the Postmaster General of the United Kingdom.

Manner of conducting tests.

## Rule 12

## SCHEDULE 5

## TOOLS, MEASURING INSTRUMENTS, SPARE PARTS, ETC.

*Part I.—Radiotelegraph Fishing Boats*

## TOOLS

- 1 Contact burnisher ;
- 1 6 in. smooth file ;
- 1 jointing knife ;
- 1 pair 7 in. wireman's insulated pliers ;
- 1 pair 6 in. long nose pliers with side cutters ;
- (a) 1 insulated screwdriver, not less than 8 in. in length, with  $\frac{1}{4}$  in. blade ;
- (a) 1 insulated grip screwdriver with  $\frac{1}{8}$  in. blade ;
- (a) 1 watch screwdriver with  $\frac{1}{16}$  in. blade ;
- (a) 1 set of spanners (Flat and Box) sizes 0, 2, 4, 6 and 8 B.A. ;
- (a) 1 spanner adjustable to 1 in. gap ;
- (b) 1  $\frac{1}{4}$  in. hand drill ;
- (b) 1 set of high-speed twist drills, tapping and clearance sizes 0-8 B.A. ;
- 1 clamp vice ;
- 1 electric soldering iron to suit fishing boat's voltage with a power consumption of not less than 40 watts or more than 70 watts ;

SCH. 5.

- 1 electric soldering iron to suit fishing boat's voltage with a power consumption of not more than 25 watts;
- 1 dusting brush;
- 1  $\frac{1}{2}$  lb. ball pane hammer;
- 1 hacksaw and blades;
- A tool box or compartment for containing the foregoing tools and capable of being locked.

#### MEASURING INSTRUMENTS

- 1 hydrometer;
- 1 dipping fahrenheit thermometer;

An ammeter capable of measuring direct current from 1 milliampere to 500 milliamperes; a voltmeter capable of measuring alternating and direct current voltage from 1 volt to 1,000 volts; and an ohm-meter capable of measuring resistance from 10 ohms to 20,000 ohms; provided that a measuring instrument in which the requirements for an ammeter, a voltmeter and an ohm-meter specified above are combined may be substituted for the said instruments.

#### SPARE PARTS AND SPARE EQUIPMENT

- 1 set of brushes for each machine installed;
- 3 cartridges for each cartridge fuse in use;
- 1 main aerial made up (wire only);
- 50 per cent. of the number of insulators in use (excluding lead-in insulators);
- 100 per cent. of the number of shackles and timbles in use;
- 12 bulldog grips to suit the aerial wire;
- 1 set of telephones and leads (with plugs if used) for each type of telephones and leads in use;
- 1 valve for each two of the first six of each type of valve in use, and then
- 1 valve for each additional 3 valves or part of 3 valves of that type in use;
- 3 vibrators for each type of vibrator in use;
- 1 indicator lamp for each indicator lamp in use;
- 1 emergency lamp;
- 1 charging mat if a mat-type charging unit is in use.

#### MISCELLANEOUS ITEMS

- 4 ozs. petroleum jelly;
- 3 sheets glass paper;
- 8 ozs. resin-cored solder;
- 4 ozs. insulating tape;
- 2 ozs. lubricating oil for general purposes;
- (c)  $\frac{1}{2}$  pint lubricating oil;
- $\frac{1}{2}$  lb. grease suitable for machine in use;
- 10 yards of each rating of fuse wire, 1 ampere, 5 ampere and 15 ampere;
- 4 ozs. copper binding wire;
- 6 yards flexible wire (5 ampere) for adjustable connections;
- 4 ozs. trichloroethylene for contact cleaning.

(a) Where special nuts and screws are used for fastening, suitable tools shall be provided.

(b) These items need not be provided in fishing boats other than those engaged on international voyages.

(c) This item need only be supplied where a machine lubricated with oil forms part of the installation.

## Rule 21 (f)

### Part II.—Radiotelephone Fishing Boats

#### TOOLS

- 1 6-in. smooth file;
- 1 jointing knife;
- (a) 1 Insulated screwdriver, not less than 8 in. in length, with  $\frac{1}{4}$  in. blade;
- (a) 1 spanner adjustable to 1-inch gap;
- 1 hacksaw and blades.

#### MEASURING INSTRUMENTS

- 1 hydrometer.

#### SPARE PARTS AND SPARE EQUIPMENT

50 per cent of the number of insulators in use (excluding lead-in insulators).

#### MISCELLANEOUS ITEMS

10 Yards of each rating of fuse wire, 1 ampere, 5 ampere and 15 ampere.

(a) Where special nuts and screws are used for fastening, suitable tools shall be provided.

## Rule 13

### SCHEDULE 6.

#### RADIOTELEGRAPH AUTO-ALARM EQUIPMENT

1.—(1) The radiotelegraph auto-alarm equipment (in this Schedule referred to as "the equipment") shall— General.

(a) include an audible alarm system, a receiver, a test signal generator, monitoring facilities and a selector;

(b) in the absence of interference of any kind be capable without manual adjustment of giving audible warning of the receipt of radiotelegraph alarm signal transmitted on a frequency of 500 kc/s and consisting of a series of twelve consecutive dashes, each with a duration of four seconds and separated by intervals of one second; in each case subject to the tolerances specified in paragraph 7 of this Schedule, provided that the strength of the signal at the receiver input is greater than 100 microvolts and less than 1 volt.

## Sch. 6.

(2) In order that the equipment shall distinguish an alarm signal in the presence of interfering signals automatic control of receiver gain shall be provided.

## Audible alarm system.

2.—(1) An audible alarm system shall have provision to operate simultaneously a bell on the bridge, a bell in the radiotelegraph room and a bell in the sleeping room of the radiotelegraph operator.

(2) The audible alarms shall be actuated by a radiotelegraph alarm signal or shall operate in the event of a sustained failure of the power supply.

(3) Only one switch for stopping the audible alarms shall be provided and this shall be situated in the radiotelegraph room.

## Receiver.

3.—(1) The receiver shall be suitable for the reception of Class A1 emissions and of Class A2 and B emissions having a note frequency between 400 and 1400 c/s, the carrier wave being in the frequency range 496 to 504 kc/s.

(2) The radio frequency response of the receiver shall be uniform to within 3db in the frequency band 496 to 504 kc/s.

(3) The receiver when in use shall not produce a field exceeding 0.1 microvolt per metre at a distance of one mile from the receiver.

## Test signal generator.

4. For the purpose of regularly testing the equipment it shall include a generator pretuned to a frequency within plus or minus 3 kc/s, of 500 kc/s, a manual key of a non-locking type and means for connecting the automatic keying device specified in Part III of Schedule 2 of these Rules.

## Monitoring facilities.

5. The receiver shall have provision for headphone and loudspeaker reception of Class A2 emissions.

## Selector.

6.—(1) The selector in conjunction with the receiver shall—

(a) accept dashes of from 3.5 seconds to 6.0 seconds duration and spaces between dashes of not more than 1.5 seconds duration, and

(b) reject dashes of a duration of 3.4 seconds or less or dashes of 6.2 seconds or greater and spaces between dashes of 1.6 seconds or greater duration.

(2) The selector shall actuate the audible alarms only after correct registration of a chosen number of consecutive dashes. The chosen number of consecutive dashes shall be either three or four. Correct registration of the fourth consecutive dash may include any time of duration of the fourth dash greater than 3.5 seconds.



**SCHEDULE 7**  
**TABLE OF WATCH HOURS**

Zones (1)	Western Limits (2)	Eastern Limits (3)	Hours of Watch Greenwich Mean Time			
			16 hours (4)		8 hours (5)	
A.—Eastern Atlantic Ocean, Mediterranean, North Sea, Baltic.	Meridian of 30° W., Coast of Greenland.	Meridian of 30° E. to the South of the Coast of Africa, Eastern limits of the Mediterranean, of the Black Sea, and of the Baltic, Meridian of 30° E. northwards from the coastline of Norway.	From 0h. To 6h. 8h. 14h. 16h. 18h. 20h. 22h.		From 8h. To 10h. 12h. 14h. 16h. 18h. 20h. 22h.	
B.—Western Indian Ocean, Eastern Arctic Ocean.	Eastern limit of Zone A.	Meridian of 80° E. Western Coast of Ceylon to Adam's Bridge, thence westward round the coast of India, Meridian 80° E. to northwards from the coastline of the U.S.S.R.	0h. 2h. 4h. 10h. 12h. 14h. 16h. 18h. 20h. 24h.		4h. 6h. 8h. 10h. 12h. 14h. 16h. 18h.	
C.—Eastern Indian Ocean, China Sea, Western Pacific Ocean, Eastern Arctic Ocean.	Eastern limit of Zone B.	Meridian of 160° E. as far as the coast of Kamchatka, Meridian of 160° E. northwards from the coastline of the U.S.S.R.	0h. 6h. 8h. 10h. 12h. 14h. 16h. 22h.		0h. 2h. 4h. 6h. 8h. 10h. 12h. 14h.	
D.—Central Pacific Ocean	Eastern Limit of Zone C.	Meridian of 140° W.	0h. 2h. 4h. 6h. 8h. 10h. 12h. 18h. 20h. 24h.		0h. 2h. 4h. 6h. 8h. 10h. 20h. 22h.	
E.—Eastern Pacific Ocean	Eastern limit of Zone D.	Meridian of 90° as far as the coast of Central America, thence Western coast of Central America and of North America.	0h. 2h. 4h. 6h. 8h. 14h. 16h. 22h.		0h. 2h. 4h. 6h. 16h. 18h. 20h. 22h.	
F.—Western Atlantic Ocean and Gulf of Mexico.	Meridian of 90° W., Gulf of Mexico, Eastern coast of North America.	Meridian of 30° W. coast of Greenland.	0h. 2h. 4h. 10h. 12h. 18h. 20h. 22h.		0h. 2h. 12h. 14h. 16h. 18h. 20h. 22h.	

## SCHEDULE 8

Rule 17

## FORM OF RADIOTELEGRAPH LOG-BOOK

## Part I. Radio telegraph Log.

<i>Name of Ship</i>	<i>Official Number and International Call Sign</i>	<i>Port of Registry</i>	<i>Gross Tonnage</i>

Name of Company operating the Radio Service.....

<i>Port at which and date when voyage commenced</i>	<i>Nature of the voyage or employment</i>	<i>Port at which and date when voyage terminated</i>
Date..... Port.....		Date..... Port.....

Delivered to the Superintendent of the Mercantile Marine Office at the Port of.....  
 on the.....date of.....19.....together with Radio-  
 telegraph Log Part II, serial numbers.....to

Countersigned.....

Master

Superintendent.....Address

## SECTION A—PARTICULARS OF RADIO STAFF

<i>Name</i>	<i>Home Address</i>	<i>Certificate Number and Class</i>



<i>Name of Ship</i>	<i>Official Number and International Call Sign</i>	<i>Port of Registry</i>	<i>Gross Tonnage</i>

Serial No. .... from ..... to .....

Name of Company operating the Radio Service .....

S.S. ....  
M.V. ....

## DIARY OF THE RADIOTELEGRAPH SERVICE

<i>Date and Time (G.M.T.)</i>	<i>Station From</i>	<i>Station To</i>	<i>Full Details of Calls, Signals and Distress Working as prescribed by Rule 19</i>	<i>Frequency</i>

## SCHEDULE 9

## Rule 25

## FORM OF RADIOTELEPHONE LOG-BOOK RADIOTELEPHONE LOG

<i>Name of Ship</i>	<i>Official Number</i>	<i>Port of Registry</i>	<i>Gross Tonnage</i>



Name of Company operating the Radio Service.....

Period covered by Log—From.....to.....

Delivered to the Superintendent of the Mercantile Marine Officer at the Port of.....

..... on the..... date of..... 196.....

Countersigned.....Master

.....  
Superintendent

.....  
Address

Address.....

#### SECTION A—PARTICULARS OF RADIOTELEPHONE OPERATORS

<i>Name</i>	<i>Home Address</i>	<i>Certificate Number and Class</i>

S.S. ....  
M.V. ....

#### SECTION B—DIARY OF THE RADIOTELEPHONE SERVICE

<i>Date and Time (G.M.T.)</i>	<i>Station From</i>	<i>Station To</i>	<i>Frequency Used</i>	<i>Record of Working as prescribed by Rule 27</i>

## Rule 10

## SCHEDULE 10

## RANGE OF RADIOTELEGRAPH TRANSMITTERS

Calculation  
of normal  
range.

1. For the purposes of this Schedule the normal range of a radiotelegraph transmitter when determined by calculation on a frequency of 500 kc/s, shall be calculated in the manner specified in paragraph 2 or paragraph 3 of this Schedule.

Effective  
radiation  
current etc.

2.—(1) In the case of all types of transmitting aerials, except "L" and "T" types, the produce of ( $I_e$ ) the effective radiation current in amperes and ( $H_e$ ) the effective height in metres of the aerial shall be calculated and converted to miles in accordance with the following table :—

Product in metre-amperes								Equivalent in miles
56	..	..	..	..	..	..	..	175
44	..	..	..	..	..	..	..	150
21	..	..	..	..	..	..	..	100
15	..	..	..	..	..	..	..	75
5	..	..	..	..	..	..	..	25

(2) The effective radiation current ( $I_e$ ) shall be obtained by multiplying the root mean square (RMS) current in amperes fed into the aerial system

by a factor  $\frac{C_r}{C_t}$  which shall be determined by the ratio of the radiation capacitance ( $C_r$ ) to the total measured capacitance ( $C_t$ ).

(3) The radiation capacitance ( $C_r$ ) shall be obtained from the product of the radiation length ( $L_r$ ) and capacitance per unit length as given in the following table :—

Radiation Length ( $L_r$ ) Diameter of aerial	pF per metre
25	15.4
35	14.0
50	12.9
70	11.9
100	11.1
200	9.8
400	8.7
600	8.2
800	7.8
1,500	7.2
3,000	6.6
6,000	6.0
10,000	5.7

(4) The radiation length shall be as follows :—

- (a) Single vertical aerial without capacitive loading  
Radiation length ( $L_r$ ) = measured length of aerial in metres ;

(b) Single vertical aerial with top capacitive loading  
Radiation length ( $L_r$ ) = measured length of aerial + 2 times the diameter of loading structure in metres ;

(c) Other types of aerial  
Radiation length ( $L_r$ ) = total length of conductor (vertical and horizontal).

(5) The radiation capacitance of  $N$  similar vertical aerials joined in parallel shall be taken to be  $N$  times the radiation capacitance of one provided the spacing between them is greater than  $\frac{L}{4}$ .

(6) The total capacitance ( $C_t$ ) of the aerial shall be obtained by measurement using a capacitance bridge.

(7) The  $\frac{C_r}{C_t}$  shall be multiplied by the measured RMS current in amperes feed into the aerial system to give the effective radiation current ( $I_e$ ).

(8) The effective height of the aerial ( $e$ ) shall be obtained by measurement of the vertical distance from the mean level of the surface of the water in which the fishing boat is afloat, to the base of the aerial, plus half the radiation length ( $L_r$ ) of the aerial or its physical height, whichever is the smaller.

3. In the case of transmitting aerials of the "L" and "T" types the product of the root mean square current in amperes at the base of the main aerial and the maximum height in metres of the aerial measured from the mean level of the surface of the water in which the fishing boat is afloat, shall be converted to miles in accordance with the following table :—

Root mean square current.

Product in metre-amperes							Equivalent in miles
102	..	..	..	..	..	..	175
76	..	..	..	..	..	..	150
45	..	..	..	..	..	..	100
34	..	..	..	..	..	..	75
10	..	..	..	..	..	..	25

## SCHEDULE II

Rule 26

### PORTABLE RADIO EQUIPMENT FOR SURVIVAL CRAFT

1.—(1) The portable radio equipment for survival craft (in this Schedule referred to as "the equipment") shall be capable of use in both lifeboats and liferafts.

General.

(2) The equipment shall be so designed that it can be used in an emergency by an unskilled person.

## SCH. 11.

(3) The entire equipment, including the aerals specified in paragraph 6 of this Schedule, shall be contained in a single unit and shall not exceed 30 lbs. in weight.

(4) The equipment shall be watertight and capable of floating in water. Means shall be provided on the equipment for lowering but it shall be capable of being dropped in the store condition from a height of 30 feet into water without damage.

(5) Provision shall be made for securing the equipment, in the operating condition, to the person of the operator.

## Transmitter.

2.—(1) The equipment shall include a transmitter capable of sending continuously, but not simultaneously, Class A2 emissions on 500 and 8364 kc/s and Class A3 emissions on a frequency of 2182 kc/s.

(2) The equipment shall supply power of at least 10 watts input to the anode of the final stage or a radio frequency output of at least 2.0 watts (A2 emission) at 500 kc/s into an artificial aerial having an effective resistance of 15 ohms and 100 picofarads capacitance in series.

(3) In addition to a key for manual transmission, the transmitter shall be provided with an automatic keying device for the transmission of the radiotelegraph alarm and distress signals and two dashes each of 10 to 15 seconds duration.

(4) The facilities for transmission of the frequency of 2182 kc/s shall include a device for the generation of the radiotelephone alarm signal specified in Part II of Schedule 3 of these Rules except that the duration of the radiotelephone alarm signal may be determined by manual control.

(5) When Class A2 emissions are being transmitted, the carrier wave shall be modulated to a depth of 100 per cent by an approximately rectangular wave of frequency between 450 and 1,350 c/s so that the carrier wave is switched on for 30 to 50 per cent of a modulation cycle.

(6) When Class A3 emissions are being transmitted, full modulation of the carrier wave by speech shall be possible.

## Receiver.

3.—(1) The equipment shall include a receiver capable of receiving on 500 and 2182 kc/s.

(2) When the receiver is operating on 500 kc/s it shall be fixed tuned and suitable for reception of Class A2 emissions over the band 495 to 505 kc/s.

(3) When the receiver is operating on 2182 kc/s it shall be fixed tuned and suitable for reception of Class A3 emissions over the band 2177 to 2187 kc/s.

(4) The receiver shall be used with headphones that are watertight and of a form designed to exclude extraneous noise. These headphones shall be permanently attached to the receiver.

## Man-powered generator.

4.—(1) The equipment shall include a man-powered generator capable of generating all the required electrical power.

(2) Means shall be provided, visible at all times, to indicate that the generator is being operated within the normal range of generator speeds.



(3) The generator shall be so designed that it can be operated by one person or by two persons simultaneously, and that it cannot be rotated in the wrong direction.

5. The equipment shall include—

(a) a single-wire aerial consisting of between 25 to 30 feet of high-conductivity stranded or braided wire capable of being supported from a lifeboat mast without the use of topmasts at the maximum practicable height, and

(b) a collapsible rod aerial at least 16 feet in height or an alternative aerial of approved design, the base of which should not be greater than two inches in diameter, capable of being easily and quickly installed in a lifeboat and in a life craft.

Aerials.

6.—(1) All manual controls shall be of such size and form as to permit normal adjustment being performed by a person wearing thick gloves. The number of manual controls shall be kept to a minimum.

Controls.

(2) The equipment shall incorporate manual send/receive switching and where necessary, in order to provide rapid changeover from "receive" to "send" there shall be a "transmitter standby" switch position.

(3) The operation of the manual controls shall not be impeded by nor shall it impede the generation of electrical energy.

7. The transmitter shall be ready for full-power operation within 30 seconds of switching on.

Operating facilities.

8. There shall be provided—

(a) an artificial aerial within the equipment for short period testing of the transmitter on full-power; and

(b) means for testing the automatic transmission facilities without the generation of radio-frequency energy.

Transmitter testing.

MADE at Lagos this 8th day of November 1967.

J. S. TARKA,  
Commissioner for Transport

#### EXPLANATORY NOTE

*(This Note does not form part of the above Rules, but is intended to explain their purpose)*

These Rules require sea-going fishing boats of more than 140 feet in length registered in Nigeria to be provided with either a radiotelephone installation or a radiotelegraph installation.

They set out the requirements which have to be complied with as respects the radio installation, the number and qualifications of radio operators to be carried, the radio watch and the duties of radio operators, including the duty of keeping a radio log-book.